

VX-4500/4600 Series

VHF/UHF Mobile Radios

SPECIFICATION SHEET

Optimised Mobile Communications

The VX-4500/4600 mobile radios are packed with enhanced features and signaling performance for increased communications flexibility and worker safety.

Expanded Signaling and Security

Both radios provide a full range of signaling capabilities including DTMF, 2-tone, 5-tone and MDC 1200® encode/decode for selective calling.

Private communication is supported by built-in **voice inversion encryption**. And, if a radio is ever lost or stolen, 5-tone **remote stun/kill/revive** can be activated to ensure messages are only heard by those intended.

Enhanced Audio Performance

These radios feature **Multi-lingual Channel Announcement**, which loudly speaks the current channel description to simplify changing channels. Alternatively record your own announcements to allow easier navigation.

Also included is **Voice Activation (VOX)** that enables users to transmit voice without pressing the Push to Talk button on the microphone. Enables hands-free operation for convenience.

In noisy environments, activate the **Clear Voice function** to enhance audio transmit to ensure your message is heard. And, to ensure a radio is not accidentally turned down too low, a minimum volume limit can be programmed by your Dealer.

Whisper capability is also included to augment audio transmit when talking quietly is necessary for discreet communications.

Record and store up to 120 seconds of voice messages for keeping an audible record of important communications using the optional DVS-8 **Voice Storage** unit.

When Safety Counts

As with all Vertex Standard mobile radios, the VX-4500/4600 Series includes **Emergency Alert** for enhanced driver safety.

Operators can activate the **Lone Worker** function when leaving equipment or a vehicle temporarily. If a problem arises while away, the radio switches to Emergency mode to alert help.

When constant contact is required at all times, Vertex Standard's exclusive **Auto-Range Transpond System II (ARTS II™)** is also included to inform the user that other ARTS II - equipped radios are within communication range.

Large Group Communications Made Easy to Manage

The VX-4600 has **512-channel capacity** and 32 groups to easily manage a variety of calls at the most complex job site. For smaller operations, the VX-4500 features 8 channels.



VX-4600

VX-4500



The Vertex Standard Difference

Our number one goal is achieving superior customer satisfaction by delivering products and services that exceed your expectations. Vertex Standard radios are built to last and are backed by a comprehensive warranty – another great reason to choose Vertex Standard. Ask your Dealer for more details.

Additional Features

- Six programmable keys
- 8-Character alphanumeric display (VX-4600)
- RSSI signal strength indicator (VX-4600)
- DTMF Paging
- DTMFANI
- Speed dial (VX-4600)
- CTCSS / DCS Encode and Decode
- BCLO / BTLO and TOT Functions
- 2 tone encode/decode
- 5 tone encode/decode
- MDC 1200® encode/decode
- Compander
- Direct channel entry (VX-4600)
- Minimum volume control
- Talk around
- Priority scan
- Dual priority scan
- Dual watch scan
- Follow-me scan
- Talk around scan
- Talk back scan
- Operator selectable scan
- Group scan
- Manual squelch control
- D-sub 15 pin accessory connector
- Public address / horn alert
- Radio-to-radio cloning
- Audible channel announcement (customisable)

Accessories

- MH-67A8J: Standard microphone
- MH-75A8J: Keypad microphone (16 keys)
- MD-12A8J: Desktop microphone
- MLS-100: External speaker, square, 12W
- FP-1023A: External power supply
- LF-6: DC Line filter
- RMK-4600: Remote mount kit

Option Board

- DVS-8: Digital voice storage

www.vertex-standard-emea.com

VX-4500/4600 Series Specifications



	VHF	UHF
General Specification		
Frequency Range	134 - 174MHz	400 - 470MHz 450 - 520 MHz
Number of Channels and Groups	512 with 32 groups (VX-4600) 8 (VX-4500)	
Power Supply Voltage	13.6V DC ± 20%	
Channel Spacing	12.5 / 20 / 25 kHz	
PLL Steps	1.25 / 2.5 / 5 / 6.25 kHz	5 / 6.25 kHz
Current Consumption	TX: 1 I A, RX: 2.5 A, Standby: 200 mA	
Operating Temperature Range	-30° C to +60° C (-22° F to +140° F)	
Frequency Stability	±2.5 ppm	
RF Input-Output Impedance	50 Ohms	
Dimension (H x W x D)	165 x 45 x 155mm (6.5 x 1.8 x 6.1 inches)	
Weight (Approx.)	1.25 kg (2.8 lbs)	
Receiver Specification: measured by EN 300 086		
Sensitivity 12dB SINAD	0.25 µV	
Adjacent Channel Selectivity	75 dB / 70 dB	
Hum and Noise	45 dB / 40 dB	
Intermodulation	75 dB	
Spurious and Image Rejection	85 dB / 80 dB	
Audio Output	Internal: 4W @ 20 Ohms; External: 12W @ 4 Ohms, <5% THD	
Transmitter Specification: measured by EN 300 086		
Output Power (Selectable)	50 / 25 / 12.5 / 5 W	45 / 25 / 12.5 / 5 W
Modulation	16K0F3E, 11K0F3E	
Maximum Deviation	±5.0 kHz / ±2.5 kHz	
Hum and Noise	45 dB / 40 dB	
Audio Distortion	< 3% @ 1 kHz	
Conducted Spurious Emission	70 dB below carrier	

Applicable MIL-STD (Pending Test Completion)

Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures	MIL 810G Methods/Procedures
Low Pressure	-	500.2 / Procedure I	500.3 / Procedure I	500.4 / Procedure I	500.5 / Procedure I
High Temperature	501.1 / Procedure I, II	501.2 / Procedure I	501.3 / Procedure I	501.4 / Procedure I	501.5 / Procedure I
Low Temperature	502.1 / Procedure I	502.2 / Procedure I, II	502.3 / Procedure I, II	502.4 / Procedure I, II	502.5 / Procedure I, II
Temperature Shock	503.1 / Procedure I	503.2 / Procedure II	503.3 / Procedure I	-	-
Solar Radiation	-	-	505.3 / Procedure I	505.4 / Procedure I	-
Rain	506.1 / Procedure II	506.2 / Procedure II	506.3 / Procedure II	506.4 / Procedure III	506.5 / Procedure III
Humidity	507.1 / Procedure II	507.2 / Procedure II	507.3 / Procedure II	-	-
Salt Fog	-	509.2 / Procedure I	509.3 / Procedure I	509.4 / Procedure I	509.5 / Procedure I
Dust	-	-	510.3 / Procedure I	-	-
Vibration	514.2 / Procedure VIII, X	514.3 / Cat. 10	514.4 / Cat. 10	514.5 / Cat. 20, 24	514.6 / Cat. 20, 24
Shock	516.2 / Procedure I, III, V	516.3 / Procedure I, IV	516.4 / Procedure I, IV	516.5 / Procedure I, IV	516.6 / Procedure I, IV

Specifications are subject to change without notice or obligation.

VERTEX STANDARD is registered in the US Patent & Trademark Office. All other product or service names are the property of their respective owners. © Vertex Standard Co. Ltd. 2011 CESS_4500/4600_04/2011