HKVN4830A WAVE PTX MULTI TENANT RADIO GATEWAY SOFTWARE - TIER 1

DESCRIPTION

- WAVE PTX Radio Gateway Software License
- Single gateway can connect one or multiple WAVE customers to one radio system
- Voice and Radio ID's only
- Inlcudes MSI remote software install and onboarding service via VPN
- One time setup of the Interop Talkgroups
- MOTOTRBO Capacity Plus, LCP, Capacity Max, Connect Plus, IPSC, DIMETRA Express
- Partner to provide specified platform and arrange access
- TIER 1 = **10 Talkpaths** only (10 concurrent calls; inc private calls and groups calls) FEATURES
 - **Multi Tenancy** This is a new feature only with the software gateway. Example; if you have one MOTOTRBO Capacity Max system installed at an airport that is being used by 10 separate airline customers, this service will enable individual airline customers to connect their own WAVE PTX customer account, to their specific MOTOTRBO Cap Max Talkgroup(s).
 - •
 - **IP Wireline Connectivity** Connect the gateway to the radio system via IP. Providing a stable and simple connection.
 - ٠
 - Voice and Radio ID Interop The software gateway currently passes voice and Radio ID's between the WAVE server and the Radio System, so you can hear and see who is calling from both systems.

COMPATIBILITY

Systems supported (connecting via wireline (IP) interface into repeater infrastructure)

- MOTOTRBO IP Site Connect
- MOTOTRBO Capacity Plus (Single Site)
- MOTOTRBO Capacity Plus (Multi Site)
- MOTOTRBO Capacity Max
- DIMETRA Express

NAI not required for this application. CAP MAX interop requires VRC Gateway and talkpaths. Currently Voice and Radio ID transfer only.

Minimum PC Requirements for TIER 1 below:

